

B615

Grab bar

Wall-mounted 135° curved grab rail Ø32mm, 3 fixation points with invisible fixings. Suitable for intensive use in community or hospital environments.



References	Side	Finishes
B615-S	Right/Left	Brushed stainless steel
B615-B	Right/Left	Polished stainless steel
B615-N	Right/Left	Matte black finish
B615-W	Right/Left	White Steel

Characteristics

Finishes	Brushed stainless steel (S) / Polished stainless steel (B) / Matte black finish (N)
Dimensions	Ø32 x 400/400mm
Fixing points	3
Maximum charge	150kg
Fixations supplied	No (installer must select correct fittings appropriate to the wall construction)
Warranty	25 years

Optional accessories

No optional accessories.

Installation info

Fixation

The rail is to be installed in accordance with the current regulations in force. The rail must be mounted with fixings appropriate to the wall construction.

Maintenance

Never use products containing hydrochloric acid, formic acid, acetic acid or bleach containing chlorine. Never use abrasive products or tools (scouring liquid, scouring sponge, dish sponge, stainless steel ball, etc.). Use of any prohibited cleaning or maintenance products or substances could damage the surface of the grab bar. Only use soap and water when cleaning the surface of the taps and then wipe dry with a clean cloth or towel. When cleaning other areas of the washroom, the grab bars should be protected from any splattering of the products that are used.

Certifications

CE

Related products

Jumbo toilet paper dispenser	H145
Wall mounted toilet brush holder set	A850

Related documents

Installation manuel	contact@duten.fr
Certifications	contact@duten.fr

Technical diagram

