

R375-S

Single-lever mixer tap

Single-lever mixer tap in solid AISI 304 stainless steel, for deck-mounted installation. Ceramic cartridge and Néoperl aerator.



References	Finish
R375-S	Brushed stainless steel
R375-B	Polished stainless steel
R375-N	Matte-black
R375-L	Brass

Characteristics	
Finishes	Brushed stainless steel (S) / Polished stainless steel (B) / Matte-black (N) / Brass (L)
Dimensions	Ø43 x H158 x D149mm
Min/Max water inlet pressure	0.5 - 12 bars
Debit	6L/min (possibility of 1.89L/min)
Aerator	SSR PCA Stream (6L/min) – cascade jet
Water inlet	2 inlets for cold and hot water
Maximum temperature	70°C
Flexible length	45cm
Warranty	10 years

Optional accessories

No optional accessories.

Installation info

Cutout

The R375 is designed to be installed on a deck with a maximum thickness of 30mm. Drill a hole with a diameter of 32-34mm.

Water inlet

Before connecting the faucet to the water circuit, run water to flush the pipes and clean them of any possible dirt.

Maintenance

For optimum care of duten faucets, use a soft cotton cloth and dampen it if necessary. Never use products containing hydrochloric acid, formic acid, acetic acid or bleaching products containing chlorine. Never use abrasive products or tools (scouring liquid, scouring sponge, abrasive dishwashing sponge, stainless steel ball, etc.).

Certifications

CE

Related products

Soap dispenser S223

Related documents

Installation manuel contact@duten.fr
Certifications contact@duten.fr

Technical diagram

